

## A-550C100

ON-OFF SWITCH DISCONNECTOR 1P. 250A D3

<b>Code</b>	009A-550C100
<b>EAN</b>	8430892215275

---

**Product description**

Cam switch-disconnector, IP20 with 0-1 red front plate 64x64 for panel fixing. 1 pole 250A. Size D3. Ergonomic screwless quick-mount handle. Cable lug terminal connection for 120 mm<sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

---

## Logistic data

Customs code	85365080
ETIM code	EC000216
Package units	1

## Technical data



Poles	1
Operational rating (I <sub>e</sub> )	250 A
Thermal rating (I <sub>th</sub> )	250 A
Wire section flexible	120 mm <sup>2</sup>
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	250 A (415 V)
	250 A (500 V)
Conditional shortcircuit current (I <sub>cc</sub> )	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	75 kW (3x230 V)
	132 kW (3x415 V)
	160 kW (3x500 V)
Mixed load AC-22A	75 kW (3x230 V)
	132 kW (3x415 V)
	132 kW (3x500 V)
Motor load AC-23A	75 kW (3x230 V)
	110 kW (3x415 V)
Standard	IEC 60947-3
Handle type	Directo

## Connection



Dimensions

