

AB5522146

ON-OFF SWITCH DISCONNECTOR 3 P.25A.WITH UNDERVOLTAGE RELEASE 400 V AC



| | |
|----------------------------|---|
| Code | 009AB5522146 |
| EAN | 8430892157391 |
| Product description | On-Off switch disconnecter with undervoltage release 400V. Red/yellow padlockable handle panel fixing 66x66. 3 poles 25A. IP20 terminal connection for wires size 1-2,5 mm ² . |

Logistic data

Customs code 85365080

Technical data

| | |
|-------------------------|-------------------------|
| Poles | 3 |
| Operational rating (Ie) | 25 A |
| Thermal rating (Ith) | 25 A |
| Wire section (AWG) | 10 |
| Wire section rigid | 2,5 - 6 mm ² |
| Wire section flexible | 2,5 - 6 mm ² |
| Tightening torque | 1,6 Nm |
| Connection screws | M4 |

Terminal



| | |
|------------------------------|-----------------|
| Max. fuse protection (gG/aM) | 25/25 A (415 V) |
| | 25/25 A (500 V) |

| | |
|--|--------------|
| Conditional shortcircuit current (Icc) | 6 kA (415 V) |
| | 6 kA (500 V) |

| | |
|-------------------------|-----|
| Insulating voltage (V~) | 690 |
|-------------------------|-----|

| | |
|---------------------------|-----|
| Insulating voltage (V...) | 400 |
|---------------------------|-----|

| | |
|--------------|-------------------|
| Dummy AC-21A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |

| | |
|-------------------|-------------------|
| Mixed load AC-22A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |

| | |
|-------------------|------------------|
| Motor load AC-23A | 5,5 kW (3x230 V) |
| | 7,5 kW (3x415 V) |
| | 11 kW (3x500 V) |

| | |
|----------|-------------|
| Standard | IEC 60947-3 |
| | UL 508 |

| | |
|-------------|---------------------|
| Handle type | Bloqueable candados |
|-------------|---------------------|

Connection

