

## AB5526126

ON-OFF SWITCH DISCONNECTOR 3 P.63A WITH UNDERVOLTAGE RELEASE 230 V AC



<b>Code</b>	009AB5526126
<b>EAN</b>	8430892157438
<b>Product description</b>	On-Off switch disconnecter with undervoltage release 230V. Red/yellow padlockable handle panel fixing 66x66. 3 poles 63A. IP20 terminal connection for wires size 1-10 mm <sup>2</sup> .

---

## Logistic data

---

Customs code 85365080

---

## Technical data

---

Poles	3
Operational rating (Ie)	63 A
Thermal rating (Ith)	70 A
Wire section flexible	16 - 50 mm <sup>2</sup>
Tightening torque	3,5 Nm
Connection screws	M8

---

### Terminal



Max. fuse protection (gG/aM)	63/63 A (415 V)
	63/63 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	22 kW (3x230 V)
	45 kW (3x415 V)
	45 kW (3x500 V)
Mixed load AC-22A	18,5 kW (3x230 V)
	37 kW (3x415 V)
	45 kW (3x500 V)
Motor load AC-23A	18,5 kW (3x230 V)
	30 kW (3x415 V)
	37 kW (3x500 V)
Handle type	Bloqueable candados

---

Connection

---

