

## ABG534100

SWITCH-DISCONNECTOR 4P.40A.D1 RED/YELLOW PADLOCKABLE HANDLE + AUXILIARY 1NO+1NC 12A



<b>Code</b>	009ABG534100
<b>EAN</b>	8430892302395
<b>Product description</b>	Padlockable on-off switch disconnecter, IP20 with red handle/yellow front plate 64x64 for panel fixing. 4 poles 40A + auxiliary contacts : simultaneous type 1NO+1NC of 12A. Size D1. Ergonomic screwless quick-mount handle. Connection with cage terminals for 6-16 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series.

## Logistic data

ETIM code	EC002611
Package units	1

## Technical data

Poles	4
Operational rating (Ie)	40 A
Thermal rating (Ith)	40 A
Wire section (AWG)	6
Wire section rigid	6 - 25 mm <sup>2</sup>
Wire section flexible	6 - 16 mm <sup>2</sup>
Tightening torque	2 Nm
Connection screws	M5

### Terminal



Max. fuse protection (gG/aM)	40/32 A (415 V)
	40/32 A (500 V)
Conditional shortcircuit current (Icc)	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	15 kW (3x230 V)
	22 kW (3x415 V)
	30 kW (3x500 V)
Mixed load AC-22A	11 kW (3x230 V)
	22 kW (3x415 V)
	22 kW (3x500 V)
Motor load AC-23A	11 kW (3x230 V)
	18,5 kW (3x415 V)
	22 kW (3x500 V)
UL Electric characteristics	2 hp 1-fase (110-120 V)
	5 hp 1-fase (220-240 V)
	7,5 hp 3-fase (220-240 V)
	10 hp 3-fase (380-415 V)
	15 hp 3-fase (440-480 V)
	20 hp 3-fase (550-600 V)
Standard	IEC 60947-3
	UL 508
Handle type	Bloqueable candados

## Connection

---

