

## A-5520TCS


COMBILIGHT ON-OFF SWITCH SIGNAL CONTROLLED TRICOLOR + BLINK. + BUZZER 240V 3P 12A



<b>Code</b>	009A-5520TCS
<b>EAN</b>	8430892267380

---

## Technical data

<b>Operational rating (Ie)</b>	12A
<b>Thermal rating (Ith)</b>	16 A
<b>Wire section (AWG)</b>	10
<b>Wire section rigid</b>	2,5 - 6 mm <sup>2</sup>
<b>Wire section flexible</b>	2,5 - 6 mm <sup>2</sup>
<b>Tightening torque</b>	1,6 Nm
<b>Connection screws</b>	M4
<b>Terminal</b>	
<b>Max. fuse protection (gG/aM)</b>	25/25 A (415 V) 25/25 A (500 V)
<b>Conditional shortcircuit current (Icc)</b>	6 kA (415 V) 6 kA (500 V)
<b>Insulating voltage (V~)</b>	690
<b>Insulating voltage (V...)</b>	400
<b>Dummy AC-21A</b>	3 kW (3x230 V) 7,5 kW (3x415 V) 11 kW (3x500 V)
<b>Mixed load AC-22A</b>	2,2 kW (3x230 V) 5,5 kW (3x415 V) 7,5 kW (3x500 V)
<b>Motor load AC-23A</b>	2,2 kW (3x230 V) 4 kW (3x415 V) 5,5 kW (3x500 V)
<b>UL Electric characteristics</b>	1 hp 1-fase (110-120 V) 1,5 hp 1-fase (220-240 V) 1 hp 3-fase (220-240 V) 2 hp 3-fase (380-415 V) 3 hp 3-fase (440-480 V) 3 hp 3-fase (550-600 V)
<b>Standard</b>	IEC 60947-3 UL 508

## Connection

---

5	6		×
3	4		×
1	2		×
552		0	1

