


A-5520TCS4

COMBILIGHT ON-OFF SWITCH SIGNAL CONTROLLED TRICOLOR + BLINK. + BUZZER 400V 3P 12A



| | |
|-------------|---------------|
| Code | 009A-5520TCS4 |
| EAN | 8430892269841 |

Technical data

| | |
|---|--|
| Operational rating (Ie) | 12A |
| Thermal rating (Ith) | 16 A |
| Wire section (AWG) | 10 |
| Wire section rigid | 2,5 - 6 mm ² |
| Wire section flexible | 2,5 - 6 mm ² |
| Tightening torque | 1,6 Nm |
| Connection screws | M4 |
| Terminal |  |
| Max. fuse protection (gG/aM) | 25/25 A (415 V) 25/25 A (500 V) |
| Conditional shortcircuit current (Icc) | 6 kA (415 V) 6 kA (500 V) |
| Insulating voltage (V~) | 690 |
| Insulating voltage (V...) | 400 |
| Dummy AC-21A | 3 kW (3x230 V) 7,5 kW (3x415 V) 11 kW (3x500 V) |
| Mixed load AC-22A | 2,2 kW (3x230 V) 5,5 kW (3x415 V) 7,5 kW (3x500 V) |
| Motor load AC-23A | 2,2 kW (3x230 V) 4 kW (3x415 V) 5,5 kW (3x500 V) |
| UL Electric characteristics | 1 hp 1-fase (110-120 V) 1,5 hp 1-fase (220-240 V) 1 hp 3-fase (220-240 V) 2 hp 3-fase (380-415 V) 3 hp 3-fase (440-480 V) 3 hp 3-fase (550-600 V) |
| Standard | IEC 60947-3 UL 508 |

Connection

| | | | |
|-----|---|---|---|
| 5 | 6 | | × |
| 3 | 4 | | × |
| 1 | 2 | | × |
| 552 | | 0 | 1 |

