

A-5522BZS2

COMBILIGHT ON-OFF SWITCH SIGNAL CONTROLLED BICOLOR + BUZZER 24V 3P 25A



| | |
|----------------------------|--|
| Code | 009A-5522BZS2 |
| EAN | 8430892266550 |
| Product description | Combilight bicolor switch disconnecter + buzzer by signal 24vdc, IP20 with 0-1 black front plate 48x48 for panel fixing, red-green LED. 3 poles 25A. Size D0. Ergonomic screwless quick-mount handle. Connection with cage terminals for 2.5-6 mm ² cable. Compatible with multiple accessories from the A5 series. |

Logistic data

| | |
|---------------|----------|
| Customs code | 85365080 |
| ETIM code | EC000216 |
| Package units | 1 |

Technical data

| | |
|-------------------------|-------------------------|
| Poles | 3 |
| Operational rating (Ie) | 25 A |
| Thermal rating (Ith) | 25 A |
| Wire section (AWG) | 10 |
| Wire section rigid | 2,5 - 6 mm ² |
| Wire section flexible | 2,5 - 6 mm ² |
| Tightening torque | 1,6 Nm |
| Connection screws | M4 |

Terminal



| | |
|--|-------------------------|
| Max. fuse protection (gG/aM) | 25/25 A (415 V) |
| | 25/25 A (500 V) |
| Conditional shortcircuit current (Icc) | 6 kA (415 V) |
| | 6 kA (500 V) |
| Insulating voltage (V~) | 690 |
| Insulating voltage (V...) | 400 |
| Dummy AC-21A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |
| Mixed load AC-22A | 7,5 kW (3x230 V) |
| | 15 kW (3x415 V) |
| | 18,5 kW (3x500 V) |
| Motor load AC-23A | 5,5 kW (3x230 V) |
| | 7,5 kW (3x415 V) |
| | 11 kW (3x500 V) |
| UL Electric characteristics | 2 hp 1-fase (110-120 V) |
| | 3 hp 1-fase (220-240 V) |
| | 2 hp 3-fase (220-240 V) |
| | 3 hp 3-fase (380-415 V) |
| | 5 hp 3-fase (440-480 V) |
| | 7 hp 3-fase (550-600 V) |
| Standard | IEC 60947-3 |
| | UL 508 |

Connection

| | | | |
|-----|---|---|---|
| 5 | 6 | | × |
| 3 | 4 | | × |
| 1 | 2 | | × |
| 552 | | 0 | 1 |

