

A-5527Tzs2

COMBILIGHT ON-OFF SWITCH SIGNAL CONTROLLED TRICOLOR + BUZZER 24V 3P 100A




Code	009A-5527Tzs2
EAN	8430892267274

Technical data

Operational rating (Ie)	100
Thermal rating (Ith)	100 A
Wire section (AWG)	16 - 1
Wire section flexible	16 - 50 mm ²
Tightening torque	3,5 Nm
Connection screws	M8

Terminal



Max. fuse protection (gG/aM)	100/100 A (415 V)
	100/100 A (500 V)
Conditional shortcircuit current (Icc)	8 kA (415 V)
	8 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	600
Dummy AC-21A	30 kW (3x230 V)
	55 kW (3x415 V)
	75 kW (3x500 V)
Mixed load AC-22A	30 kW (3x230 V)
	55 kW (3x415 V)
	55 kW (3x500 V)
Motor load AC-23A	22 kW (3x230 V)
	37 kW (3x415 V)
	45 kW (3x500 V)
UL Electric characteristics	10 hp 1-fase (110-120 V)
	15 hp 1-fase (220-240 V)
	25 hp 3-fase (220-240 V)
	30 hp 3-fase (380-415 V)
	40 hp 3-fase (440-480 V)
	50 hp 3-fase (550-600 V)
Standard	IEC 60947-3
	UL 508

Connection

5	6	X
3	4	X
1	2	X
552	0	1

