

## A-5527TZS4

COMBILIGHT ON-OFF SWITCH SIGNAL CONTROLLED TRICOLOR + BUZZER 400V 3P 100A




---

Code	009A-5527TZS4
EAN	8430892275217

---

## Technical data

<b>Operational rating (Ie)</b>	100
<b>Thermal rating (Ith)</b>	100 A
<b>Wire section (AWG)</b>	16 - 1
<b>Wire section flexible</b>	16 - 50 mm <sup>2</sup>
<b>Tightening torque</b>	3,5 Nm
<b>Connection screws</b>	M8
<b>Terminal</b>	
<b>Max. fuse protection (gG/aM)</b>	100/100 A (415 V) 100/100 A (500 V)
<b>Conditional shortcircuit current (Icc)</b>	8 kA (415 V) 8 kA (500 V)
<b>Insulating voltage (V~)</b>	690
<b>Insulating voltage (V...)</b>	600
<b>Dummy AC-21A</b>	30 kW (3x230 V) 55 kW (3x415 V) 75 kW (3x500 V)
<b>Mixed load AC-22A</b>	30 kW (3x230 V) 55 kW (3x415 V) 55 kW (3x500 V)
<b>Motor load AC-23A</b>	22 kW (3x230 V) 37 kW (3x415 V) 45 kW (3x500 V)
<b>UL Electric characteristics</b>	10 hp 1-fase (110-120 V) 15 hp 1-fase (220-240 V) 25 hp 3-fase (220-240 V) 30 hp 3-fase (380-415 V) 40 hp 3-fase (440-480 V) 50 hp 3-fase (550-600 V)
<b>Standard</b>	IEC 60947-3 UL 508

Connection

---

5	6	X
3	4	X
1	2	X
552	0	1

