

## A-561112L4

COMBILIGHT CHANGEOVER SWITCH RED/GREEN 400V 2P 16A



<b>Code</b>	009A-561112L4
<b>EAN</b>	8430892257381
<b>Product description</b>	Combilight changeover switch by position 400vac, IP20 with 1-0-2 48x48 black front plate for panel fixing, 1" green LED, "0" red LED, "2" green LED. 2 poles 16A. Size D0. Ergonomic screwless quick-mount handle. Connection with cage terminals for 2.5-6 mm <sup>2</sup> cable. Compatible with multiple accessories from the A5 series. "

---

## Logistic data

---

Customs code	85365080
ETIM code	EC000216
Package units	1

---

## Technical data

---

Operational rating (I <sub>e</sub> )	16 A
Thermal rating (I <sub>th</sub> )	20 A
Wire section (AWG)	10
Wire section rigid	2,5 - 6 mm <sup>2</sup>
Wire section flexible	2,5 - 6 mm <sup>2</sup>
Tightening torque	1,6 Nm
Connection screws	M4

---

### Terminal



Max. fuse protection (gG/aM)	25/25 A (415 V)
	25/25 A (500 V)
Conditional shortcircuit current (I <sub>cc</sub> )	6 kA (415 V)
	6 kA (500 V)
Insulating voltage (V~)	690
Insulating voltage (V...)	400
Dummy AC-21A	5,5 kW (3x230 V)
	11 kW (3x415 V)
	15 kW (3x500 V)
Mixed load AC-22A	4 kW (3x230 V)
	7,5 kW (3x415 V)
	11 kW (3x500 V)
Motor load AC-23A	3 kW (3x230 V)
	5,5 kW (3x415 V)
	7,5 kW (3x500 V)
UL Electric characteristics	1,5 hp 1-fase (110-120 V)
	2 hp 1-fase (220-240 V)
	2 hp 3-fase (220-240 V)
	2 hp 3-fase (380-415 V)
	3 hp 3-fase (440-480 V)
Standard	5 hp 3-fase (550-600 V)
	IEC 60947-3
	UL 508

---

**Connection**

---

7	8			×
5	6	×		
3	4			×
1	2	×		
561		1	0	2

