

## LCA42B107

LD CHANGEOVER SWITCH I - I+II - II 3P 200A +AC ENCLOSED

|             |               |
|-------------|---------------|
| <b>Code</b> | 009LCA42B107  |
| <b>EAN</b>  | 8430892353984 |

---

## Logistic data

---


|               |          |
|---------------|----------|
| Customs code  | 85365080 |
| ETIM code     | EC000216 |
| Package units | 1        |

## Technical data

---

|                         |                    |
|-------------------------|--------------------|
| Poles                   | 3                  |
| Auxiliary               | 1NO                |
| Operational rating (Ie) | 200 A              |
| Thermal rating (Ith)    | 200 A              |
| Wire section flexible   | 95 mm <sup>2</sup> |
| Connection screws       | M8                 |

### Terminal



|  |                   |
|--|-------------------|
| Max. fuse protection (gG/aM)           | 200 A (415 V)     |
|  | 200 A (500 V)     |
| Conditional shortcircuit current (Icc) | 8 kA (415 V)      |
|  | 8 kA (500 V)      |
| Insulating voltage (V~)                | 690               |
| Insulating voltage (V...)              | 600               |
| Dummy AC-21A                           | 55 kW (3x230 V)   |
|  | 110 kW (3x415 V)  |
|  | 132 kW (3x500 V)  |
| Mixed load AC-22A                      | 55 kW (3x230 V)   |
|  | 110 kW (3x415 V)  |
|  | 110 kW (3x 500 V) |
| Motor load AC-23A                      | 55 kW (3x230 V)   |
|  | 90 kW (3x415 V)   |
| Standard                               | IEC 60947-3       |

## Dimensions

---

