


LD563C100

LD CHANGEOVER SWITCH 4P 250A



| | |
|-------------|---------------|
| Code | 009LD563C100 |
| EAN | 8430892215268 |

Logistic data

| | |
|---------------------|----------|
| Customs code | 85365080 |
| ETIM code | EC000216 |
| Package units | 1 |
| Package height (mm) | 150 |
| Package width (mm) | 195 |
| Package length (mm) | 280 |

Technical data


| | |
|--------------------------------------|---------------------|
| Poles | 4 |
| Auxiliary | - |
| Operational rating (I _e) | 250 A |
| Thermal rating (I _{th}) | 250 A |
| Wire section flexible | 120 mm ² |
| Connection screws | M8 |

Terminal



| | |
|---|------------------|
| Max. fuse protection (gG/aM) | 250 A (415 V) |
| | 250 A (500 V) |
| Conditional shortcircuit current (I _{cc}) | 8 kA (415 V) |
| | 8 kA (500 V) |
| Insulating voltage (V~) | 690 |
| Insulating voltage (V...) | 600 |
| Dummy AC-21A | 75 kW (3x230 V) |
| | 132 kW (3x415 V) |
| | 160 kW (3x500 V) |
| Mixed load AC-22A | 75 kW (3x230 V) |
| | 132 kW (3x415 V) |
| | 132 kW (3x500 V) |
| Motor load AC-23A | 75 kW (3x230 V) |
| | 110 kW (3x415 V) |
| Standard | IEC 60947-3 |

Connection



Dimensions

